


CFM-101S SERIES

100 WATT OPEN FRAME AC-DC MODULES WITH PFC



FEATURE

- * 100W Single Output
- * Universal Input 90-264Vac
- * Active PFC Function
- * 2"X4" Size
- * Efficiency at 88% Typical
- * Continuous Short Circuit Protection
- * Meets EN55022 Class "B" and CISPR/FCC Class B, Conducted



Model	Output Voltage	Max. Load	Min. Load	Ripple & Noise Noise	Voltage Accuracy	Line Regulation	Load Regulation	%EFF
CFM-101S120	12V	8.4A	0 A	1%	+/- 1%	+/- 0.5%	+/- 1%	87% Typ.
CFM-101S150	15V	6.7A	0 A	1%	+/- 1%	+/- 0.5%	+/- 1%	87% Typ.
CFM-101S200	20V	5.0A	0 A	1%	+/- 1%	+/- 0.5%	+/- 1%	88% Typ.
CFM-101S240	24V	4.2A	0 A	1%	+/- 1%	+/- 0.5%	+/- 1%	88% Typ.
CFM-101S480	48V	2.1A	0 A	1%	+/- 1%	+/- 0.5%	+/- 1%	88% Typ.

SPECIFICATIONS

Typical at 25°C, nominal line and 75% load, unless otherwise Specified

INPUT SPECIFICATIONS:

Voltage 90~264Vac
 Frequency 47 to 63Hz
 Inrush Current 90A Max. @240Vac
 Conducted EMI CISPR/FCC Class B
 Isolation Input to output = 4,242VDC
 Leakage Current 3.5mA max.

OUTPUT SPECIFICATIONS:

Holdup Time 12mS typ. @115Vac
 Short Circuit Protection Continuous
 Temperature Coefficient $\pm 0.05\%/^{\circ}\text{C}$

GENERAL SPECIFICATIONS:

Operating Temperature 0 ~ 40°C
 Storage Temperature -20~85°C
 Cooling Natural Convection
 Humidity 0~93% at 25°C

MECHANICAL CHARACTERISTICS:

Dimensions 101.6x50.8x27.94mm(2.0x4.0x1.1Inches)
 Weight 150g

NOTE:

1. Add a 0.1uF ceramic capacitor and a 10uF E.L. capacitor to output for Ripple & Noise measuring @20MHz BW.
2. Line regulation is measured from 100Vac to 240Vac with full load.
3. Load regulation is measured from 10% to 100% full load.
4. Connectors : AC input: Molex 5277 or equivalent
 DC input: Molex 5273 or equivalent

CFM101S Series

All Dimensions In Inches[mm]

Tolerances : Inches:x.xx = ± 0.02 , x.xxx = ± 0.010
 Millimeters:x.x = ± 0.5 , x.xx = ± 0.25

